



From pavers  
to concrete

LANDSCAPE NOTES

1. ALL LANDSCAPED AREAS TO BE INSTALLED ACCORDING TO ACCEPTED BEST INDUSTRY STANDARDS.
2. PLANT MATERIALS SHALL BE OF HIGH GRADE AND SHALL MEET THE QUANTITY AND SIZE STANDARDS.
3. PLANTING WILL BE INSTALLED BETWEEN 25" AND 30" DEPTH.
4. SOIL REPLACEMENT WILL BE A 60% DUFFY COMPOST AND 40% FREE LOAM MIX. PLANTING AREA PREPARATION SEE SPEC 17.
5. SOIL WILL BE INSTALLED TO A DEPTH OF TWO FEET AND THREE FEET BELOW WALK AFTER SETTING.
6. TREES SHALL BE PROPERLY STAKED AND GUARDED TO AVOID COLLISION WITH PEDESTRIAN TRAFFIC.
7. PLANT SUBSTITUTIONS WITHOUT PRIOR APPROVAL WILL BE SUBJECT TO REVISION.
8. LANDSCAPE SHALL COMPLY WITH ODOT AND CITY OF WASHINGTON DEVELOPMENT CODES.
9. PEDESTRIAN CONTROL PLANS TO BE SUBMITTED TO ODOT WHEN WORKING FROM PUBLIC SIDEWALKS.

Revised City Project 17" x 4" to 2 1/2" H. 02/15/12

Prepared and printed. Copyright 2012. Prepared by Powell of Deep into Space CONSULTANTS on behalf of the WFO GROUP.